(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/068094 A1

(51) International Patent Classification7: B07B 13/065, A22C 25/00

(21) International Application Number:

PCT/IS2005/000002

(22) International Filing Date: 14 January 2005 (14.01.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

7117

16 January 2004 (16.01.2004)

- (71) Applicant (for all designated States except US): STYLE EHF. [IS/IS]; Midhraun 12, IS-210 Gardabaer (IS).
- (72) Inventor; and
- Inventor/Applicant (for US only): RAGNARSSON, Egill Thor [IS/IS]; Stekkjarflot 21, IS-210 Gardabaer (IS).
- (74) Agent: A & P ARNASON; Efstaleiti 5, IS-103 Reykjavik (IS).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: RIDGE-BELT GRADING APPARATUS



(57) Abstract: A grading apparatus for grading objects such as in particular fish or shrimp in respect of their size, comprising a plurality of juxtaposed substantially parallel endless conveyor belts (27), wherein the width (9) separating adjacent conveyor belts is larger at the unloading end (29) than at the loading end (28) of the belts and define sorting channels through which the items fall down when the channel width corresponds to the width of the item, each conveyor belt comprising a plurality of hinged segments with a sloping cross-section such that in between each adjacent pair of belts is formed a V-shaped valley with substantially continuous sloping sides (2), each side being at an angle in the range of about 70-85°.

WO 2005/068094 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.